4835 Optical Module

Overview

The DS4835 is a low-power, 16-bit microcontroller with a unique peripheral set supporting optical applications that require high-resolution conversion of many analog signals and digital-signal processing (DSP) of those signals, and an external host interface. RO4835T is a low-loss, spread glass reinforced, ceramic-filled thermoset laminate manufactured by Rogers Corporation. It belongs to the RO4000® series, which has become something of an industry standard for high-frequency applications that require predictable electrical performance without breaking. RO4835™ laminates are engineered to provide low loss, outstanding stability, and extended durability in demanding RF and microwave applications. These materials are specifically designed for high-frequency circuits, offering superior performance and compatibility with standard FR-4 PCB processing. Elevate your RF design with our premium RO4835 8-layer multi-layer PCB, expertly manufactured for demanding high-frequency applications. This professional-grade RF module board combines Rogers RO4835 advanced circuit material with precision engineering to deliver exceptional performance in. For applications demanding greater stability at elevated temperatures Rogers has developed RO4835TM laminate, that is significantly more resistant to oxidation than other hydrocarbon based materials. * Moreover, RO4835 material provides nearly identical electrical and mechanical properties to. RO4835TTM 2. The world has seen the ongoing evolution. OPTICAL MCU, 16BIT, 10MHZ, TQFN-40; Product Range:DS4 Family DS4830 Series Microcontrollers; Archite. Manufacturer: Maxim Integrated Products. Description: Optical Microcontroller 16-Bit MAXQ20 Low-Power Microcontroller.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Article Content

Rogers RO4835T PCB Laminate: Complete Guide to Rogers High

RO4835T comes in three standard core thicknesses: These thin profiles make it ideal for high-layer-count designs where overall board thickness is a concern, particularly in applications like phased

RO4835 High-Frequency PCB Laminates for RF, 5G

Material Properties ... Applications 5G Infrastructure: High-frequency laminates for base stations and antennas. Automotive Radar:Advanced driver

RO4835 1.5mm 2oz ENIG 8-Layer Multi-Layer RF Module Board

This professional-grade RF module board combines Rogers RO4835 advanced circuit material with precision engineering to deliver exceptional performance in telecommunications, aerospace, military,

RO4835 Laminate Data Sheet

As part of the RO4000® hydrocarbon ceramic laminate family, RO4835 laminates are designed to ofer superior high frequency performance and low cost circuit fabrication. The result is a low loss material

RO4835T Data Sheet

RO4835TTM 2.5 mil, 3 mil and 4 mil laminates are 3.3 Dk low loss, spread glass reinforced, ceramic thermoset materials that were designed as inner-layers for use in multilayer board designs, and to

DS4835 Datasheet, PDF

Description: Optical Microcontroller 16-Bit MAXQ20 Low-Power Microcontroller. 11 Results. Datasheet: 1MbKb/29P. Manufacturer: Maxim Integrated Products.

RO4835 Laminate

As part of the RO4000® hydrocarbon ceramic laminate family, RO4835 laminates are designed to ofer superior high frequency performance and low cost circuit fabrication. The result is a low loss material

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Contact Us

Continue your research online:

Website: https://cjcconsultants.co.za
Technical inquiry: https://cjcconsultants.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved