Spacing requirements between adjacent primary distribution boxes



Simplex SC UPC

Overview

Distribution Box and Selection Guide: Internal Structure, Components. Learn how to choose a distribution box and understand its internal structure, inclu.

Key Takeaways

Minimum spacing for primary distribution boxes typically requires 1 inch through air and 2 inches over surfaces for feeder circuits, with additional practical clearance for maintenance and safety.

Standard Requirements

For indoor primary distribution boxes or power distribution blocks, UL and NEC standards specify spacing based on voltage and application: Feeder circuits (ahead of branch circuit overcurrent devices): 1 inch through air and 2 inches over surfaces at 600V is required for listed power distribution blocks (UL1953) in industrial control panels, ensuring safe clearance between live parts and grounded or opposite-polarity parts (UL508A Section 10. 2 and 28. 2.

4). Recognized terminal blocks (UL1059) must meet the same spacing requirements if used in field wiring applications, with suitability depending on the group classification (A, C, or D). Branch circuits: Listed PDBs exceed spacing requirements for branch circuits, providing adequate clearance for most OEM and field applications.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Practical Considerations

Maintenance access: Adjacent boxes should allow sufficient room for personnel, tools, and equipment such as boom trucks or cable handling devices, especially for outdoor or pad-mounted units. Alignment and accessibility: Switchboards and distribution boxes may be front- or rear-accessible. When aligning multiple units, ensure offsets or gaps allow for bus maintenance, cable entry, and safe operation of overcurrent protective devices.

Environmental factors: Outdoor installations may require additional spacing to account for conductor swing, weather, and clearance from other structures or roadways.

Summary

Minimum spacing: 1 inch through air, 2 inches over surfaces for feeder circuits (UL1953 listed PDBs). Practical spacing: Additional clearance for maintenance, equipment access, and safety, often exceeding minimum standards. Compliance: Always verify spacing against UL, NEC, and local utility requirements, as well as manufacturer recommendations for specific distribution boxes or switchboards.

By following these guidelines, primary distribution boxes can be safely installed while maintaining accessibility and compliance with electrical standards.

Article Content

Distribution Box and Selection Guide: Internal Structure, Components ...

Learn how to choose a distribution box and understand its internal structure, including MCBs, busbars, neutral bars, earth bars, RCDs, RCBOs, SPDs, enclosure ratings, and wiring layout.

Minimum distance requirement between bus bars and enclosure per

My last question relates to the wording the NEC uses for spacing requirements. There are two columns in this table under section 408.56 that indicate different spacing requirements.

TB 56/1.1 Building Services Spatial Fit and MMC/DfMA

To validate services ceiling zones, plant rooms and risers, the designer and engineers should ensure that pinch points and spatial consideration is tested for all “rooms, routes and risers” (the three R''s).

National Electrical Code (NEC) Requirements for Panelboards

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Clearance: Electrical panels must be installed in a readily accessible area with a minimum clearance of 30 inches (762 mm) wide, 3 ft (36 inches or 914 mm) deep, and 6.5 feet (≈ 2 meter) high in front of

Unit Substations

Provide rear access to all unit substations. Working space for rear access shall be based upon clearances required for working on energized parts at the system voltage. Where applicable, include

IEEE 525-2007_accepted

Twisting and shielding requirements for both digital input and digital output signals vary among different manufacturers of computerized measuring systems. Separation of digital input cables and digital

GUIDELINES FOR SUBSTATION AND SWITCHROOM

Working space for access for maintenance of equipment, while keeping an adjoining section of the substation live to maintain power supply to essential loads, may require additional space between

Phase to Phase Clearance as per IEC 61439: Standard & Chart

The phase to phase clearance chart below provides a quick reference for the minimum spacing required between energized conductors at different voltage levels. These values are based

SPACING CONSIDERATIONS BETWEEN SUBSTATION

When calculations are performed, closer or greater spacing may be required than shown in spacing charts. Performing the calculations may be more accurate, but it is more time-consuming and

Electrical equipment floor space

This paper will review some of the NEC requirements regarding required electrical space and discuss new product concepts serving to reduce equipment size, resulting in reduced space requirements,

How to Choose a House Distribution Box | CHINT global

A well-chosen distribution box ensures the safety and efficiency of your household electrical system. This article guides you through selecting a distribution box.

Electrical Panel & Equipment Working Space

Electrical panel clearance distances are given by the U.S. NEC specifying working distance. Details are given here. This electrical wiring article series discusses procedures for safe and effective visual

© 2026 CJC FIBRE CONSULTANTS - All rights reserved

Electrical Clearances: Requirements and Safe Distances

Electrical clearances set the minimum safe distances for panels, overhead lines, pools, and buried wiring — and ignoring them has real

Understanding Distribution Boxes: A Comprehensive

A distribution box, also known as a power distribution box or electrical distribution box, is used to distribute electrical power safely to multiple

Clearances and Location Requirements for Enclosures, Pads, and

CLEARANCES AND LOCATION REQUIREMENTS FOR ENCLOSURES, PADS, AND UNDERGROUND EQUIPMENT Electric Distribution Function: Design

Clearance and creepage_UL-60950_IEC-60950_28_09_17.pdf

2.10.3.3 Clearances in primary circuits For insulation in PRIMARY CIRCUITS, between PRIMARY CIRCUITS and earth and between PRIMARY CIRCUITS and SECONDARY CIRCUITS, the following

Electrical Outlet Height, Clearances & Spacing

Requirements for electrical receptacle (outlet or wall plug) spacing, height, and clearances in buildings. Details about spacing, height, and clearance for

How Close Can Electrical Outlets Be to Each Other?

The primary constraint when installing two single-gang boxes is the physical space required for the box bodies, wiring connections, and faceplates. Furthermore, placing boxes too close

Contact Us

Continue your research online:

Website: https://cjcconsultants.co.za
Technical inquiry: https://cjcconsultants.co.za/contact.html

This document is for preliminary research. Verify specifications against current standards, product documentation and project requirements.

© 2026 CJC FIBRE CONSULTANTS - All rights reserved